
DATA SHEET. Model: GL-230P.

Self-contained emergency luminaire with maintained and non-maintained functioning of the G Led Series.



Description

Self-contained emergency luminaire for surface mounting, recessed mounting through a spring kit, flush mounting through a flushing frame or watertight mounting through a watertight housing.


It includes three maintained LEDs (ambient lighting) of the desired colour at the bottom of the luminaire. Illumination through LED strip with internal transparent, soft opal (-8%) or strong opal (-30%) diffuser.

Modern and sharp-edged design with external transparent, soft opal (-8%) or strong opal (-30%) diffuser.

Technical characteristics

Lamp in emergency	40 x LED White 5,700 K
Lamp in maintained	40 x LED White 5,700 K
Flux in emergency	235 lm
Flux in maintained	183 lm
Charge indicator LED	1 x LED green
Autonomy	1 h
Supply voltage	230 Vac - 50 Hz
Operation temperature	0 ÷ 40°C
Mains power maintained	5.9 W
Mains power non-maint.	3.4 W
Battery	Ni-Cd (HT) 2.4 V – 1.5 Ah
Remote controllable	Yes (TL-300)
Protection rating	IP44 - IK04
Electrical insulation	Class II
Applicable legislation	CE marking (93/68/CEE): 2014/35/EU 2014/30/EU 2011/65/EU

Photometric curve



DATA SHEET. Model: GL-230P _ Rev. 01 (February 2024)



LUZNOR Desarrollos Electrónicos, S.L.
Paduleta, 47 · 01015 · Vitoria-Gasteiz · 945 200 961
NIF: B01266451 · luznor@luznor.com · www.luznor.com



Dimensions


Surface mounting




Recessed mounting (cut: 274 x 98 mm)



Flush mounting (cut: 298 x 124 mm)



Watertight mounting



DATA SHEET. Model: GL-230P _ Rev. 01 (February 2024)



LUZNOR Desarrollos Electrónicos, S.L.
Paduleta, 47 · 01015 · Vitoria-Gasteiz · 945 200 961
NIF: B01266451 · luznor@luznor.com · www.luznor.com

