

DATA SHEET. Model: LTL-200.

Self-contained emergency lighting fitting with non-maintained functioning of the Tube Series.



Descripción


Self-contained watertight emergency lighting fitting to be surface mounted. Illumination by LED-strip with internal and external transparent diffusers. Cylindrical design with the possibility of rotation in its two lateral supports. Supplied with a PG-11 cable gland for cable entry from the side.

Technical characteristics

Lamp in emergency	4 x LED White 5,700 K
Lampara in maintained	N/A
Flux in emergency	200 lm
Flux in maintained	N/A
LED charge indicator	1 x LED green
Autonomy	1 h
Power supply voltage	230 Vac - 50 Hz
Operation temperature	0 ÷ 40°C
Mains power	1.5 W
Battery	Ni-Cd (HT) 3.6 V – 0.7 Ah
Remote controllable	Yes (TL-300)
Protection rating	IP67 - IK07
Electrical insulation	Class I
Applicable legislation	CE marking (93/68/CEE): 2014/35/EU 2014/30/EU 2011/65/EU

Photometric curve


Cd/Klm



■ 0-180 ■ 45-225 ■ 90-270 ■ 135-315

Dimensions

Surface mounting



DATA SHEET. Model: LTL-200 _ Rev. 01 (March 2024)



LUZNOR Desarrollos Electrónicos, S.L.
Paduleta, 47 · 01015 · Vitoria-Gasteiz · 945 200 961
NIF: B01266451 · luznor@luznor.com · www.luznor.com

