



# Tube Series

Cylindrical, watertight LED emergency fitting. It fits into two supports that allow the fitting to rotate, permitting the light beam to be directed. Lighting by means of LED strip with internal diffuser in high transmittance material for optimum protection of the LEDs and homogeneous and pleasant lighting.



## Non maintained

model	Φ (lm)	A (h)	LEDs	P net (W)	RRP (€)
LTL-200	200	1	4	1.5	130.04
LTL-450	450	1	9	2.6	135.35
LTL-800	800	1	16	3.0	178.85
LTL-1200	1,200	1	24	3.0	187.89
LTL-100-2	100	2	2	1.5	128.99
LTL-200-2	200	2	4	2.6	134.20
LTL-400-2	400	2	8	3.0	175.49
LTL-600-2	600	2	12	3.0	187.89
LTL-150-3	150	3	3	2.6	134.20
LTL-250-3	250	3	5	3.0	173.83
LTL-400-3	400	3	8	3.0	187.89

- ◇ Protection rating: IP67.
- ◇ Ni-Cd (HT) or Li-Ion battery, according to the model.
- ◇ The cable entry is from the side and is supplied with a cable gland size PG-11.
- ◇ Vandal-proof fastening: replacement of the two standard plastic brackets in which the luminaire fits with two screwed metal brackets.

Ref. Vandal-proof flange  
RRP. 13.75 €



## Maintained

model	Φ (lm)	A (h)	LEDs	P net (W)	RRP (€)
LTL-450P	450	1	9	7.5	146.82
LTL-200P-2	200	2	4	4.9	146.82
LTL-150P-3	150	3	3	4.4	146.82

To request the supplement of the two brackets for vandal-proof fastening, add "(AV)" to the reference. Example:

**LTL-1200 (AV)**  
└─ Fastening | Standard brackets  
(AV) Vandal-proof brackets (+18.57 €)

## Surface mounting

