DATA SHEET. Model: MB-300.

Self-contained emergency luminaire with nonmaintained functioning of the Polar Series.





Description

Self-contained emergency luminaire for flush mounting.Composed of three modules: luminaire, kit and battery.Illumination through LED crown (possibility of warm temperature colour: 3,000 K).Minimalist design with transparent, soft opal (-8%) or strong opal (-30%) diffuser.

Technical characteristics

Lamp in emergency	6 x LED white 5,700 K	Cd/Klm
Lamp in maintained	None	
Flux in emergency	300 lm	XX
Flux in maintained	None	$X \times X \setminus I$
Charge indicator LED	1 x LED green	N XXTT
Autonomy	1 h	1/XXXHA
Supply voltage	230 Vac - 50 Hz	
Operation temperature	0 ÷ 40°C	
Mains power	2.0 W	
Battery	Ni-Cd (HT) 3.6 V – 1.5 Ah	1 Ltta
Remote controllable	Yes (TL-300)	H XX/19
Protection rating	IP42 - IK08 (IP55 possible)	XX
Electrical insulation	Class II	XXX24
Applicable legislation	CE marking (93/68/CEE):	$\wedge \times \times / \sim$
-	2014/35/EU	X 7 320
	2014/30/EU	


2011/65/EU

0-180

Photometric curve

Dimensions

Flush mounting



DATA SHEET. Model: MB-300 _ Rev. 01 (March 2024)



LUZNOR Desarrollos Electrónicos, S.L. Paduleta, 47 · 01015 · Vitoria-Gasteiz · 945 200 961 NIF: B01266451 · luznor@luznor.com · www.luznor.com

