

Description

Self-contained emergency luminaire for flush mounting.

Composed of three modules: luminaire, kit and battery.

Illumination through LED crown (possibility of warm temperature colour: 3,000 K).

Minimalist design with transparent, soft opal (-8%) or strong opal (-30%) diffuser.

Technical characteristics

Lamp in emergency 6 x LED white 5,700 K

Lamp in maintained N/A
Flux in emergency 200 lm
Flux in maintained N/A

Charge indicator LED 1 x LED green

Autonomy 1 h

Supply voltage 230 Vac - 50 Hz

Operation temperature $0 \div 40^{\circ}$ C Mains power 1.5 W

Battery Ni-Cd (HT) 3.6 V - 0.7 Ah

Remote controllable Yes (TL-300)

Protection rating IP42 - IK08 (IP55 possible)

Electrical insulation Class II


Applicable legislation CE marking (93/68/CEE):

2014/35/EU 2014/30/EU

2014/30/EU 2011/65/EU


Photometric curve

Cd/Klm




Dimensions

Flush mounting



DATA SHEET. Model: MB-200 _ Rev. 01 (March 2024)





Paduleta, 47 · 01015 · Vitoria-Gasteiz · 945 200 961 NIF: B01266451 · luznor@luznor.com · www.luznor.com





