

Self-contained emergency luminaire with maintained functioning of the Polar Series.







Description

Self-contained emergency luminaire for flush mounting.

Composed of three modules: luminaire, kit and battery.

Illumination through LED crown (possibility of warm temperature colour: 3,000 K).

Minimalist design with transparent, soft opal (-8%) or strong opal (-30%) diffuser.

Technical characteristics

6 x LED white 5,700 K Lamp in emergency Lamp in maintained 6 x LED white 5,700 K

Flux in emergency 200 lm Flux in maintained 200 lm Charge indicator LED 1 x LED green

Autonomy

230 Vac - 50 Hz Supply voltage

Operation temperature $0 \div 40^{\circ}C$ 4 W

Mains power

Ni-Cd (HT) 3.6 V - 0.7 AhBattery


Remote controllable Protection rating

Electrical insulation

Applicable legislation


Photometric curve


Cd/Klm



Dimensions

Flush mounting





Yes (TL-300)

2014/35/EU 2014/30/EU 2011/65/EU


Class II

IP42 - IK08 (IP55 possible)

CE marking (93/68/CEE):

DATA SHEET. Model: MB-200P _ Rev. 01 (March 2024)





Paduleta, 47 · 01015 · Vitoria-Gasteiz · 945 200 961 NIF: B01266451 · luznor@luznor.com · www.luznor.com







