



L Led Series

The timeless design emergency luminaire. LED strip lighting (colour temperature: 5,000 K) with internal diffuser, improving the energy efficiency and the aesthetic and functional value of the classic L series. Choice of maintained or non-maintained mode. Special model with 1,200 lumens non-maintained (colour temperature: 5,700 K). Remote controllable.



Maintained / Non-maintained

model	Φ (lm)	A (h)	P net (W)	RRP (€)
LL-110P-TT	118	1	4.3 / 3.0	54.68
LL-230P-TT	235	1	5.1 / 3.0	59.56
LL-350P-TT	353	1	5.8 / 3.0	68.00
LL-470P-TT	470	1	7.1 / 3.0	80.05
LL-580P-TT	588	1	8.4 / 3.1	91.81
LL-110P-2-TT	118	2	4.3 / 3.0	61.51
LL-170P-2-TT	176	2	5.1 / 3.0	70.18
LL-230P-2-TT	235	2	5.1 / 3.0	77.41
LL-290P-2-TT	294	2	5.8 / 3.0	89.52
LL-70P-3-TT	78	3	4.3 / 3.0	61.51
LL-110P-3-TT	118	3	4.3 / 3.0	64.11
LL-150P-3-TT	157	3	5.1 / 3.0	77.41
LL-190P-3-TT	196	3	5.1 / 3.0	83.56

Special model 1,200 lm NM


model	Φ (lm)	A (h)	P net (W)	RRP (€)
LL-1200-TT	1,200	1	3.0	140.48

Surface mounting



To request a different internal and external diffuser type, change the corresponding letters in the reference. Example:

LL-470P-TS



- ◇ Internal diffuser: allows for optimum protection of the LEDs and homogeneous illumination.
- ◇ Protection rating: IP42.
- ◇ Ni-Cd (HT) battery except for the special model LL-1200, with Li-Ion battery.
- ◇ Accessories and signalling on page 34.

