
DATA SHEET. Model: LLD-200B.

Self-contained emergency luminaire with maintained functioning of the LLD Series.




Description

Self-contained emergency luminaire for flush mounting in false ceiling or hollow wall. Series consisting of an emergency luminaire of the L Basic Led series and a flushing box. Illumination through LED strip without internal diffuser. Discreet, sharp-edged design with flat opal diffuser (luminous flux -25%).

Technical characteristics

Lamp in emergency	4 x LED White 5,700 K
Lamp in maintained	4 x LED White 5,700 K
Flux in emergency	200 lm
Flux in maintained	200 lm
Charge indicator	1 x LED green
Autonomy	1 h
Supply voltage	230 Vac - 50 Hz
Operation temperature	0 ÷ 40°C
Mains power	3.9 W
Battery	Ni-Cd (HT) 3.6 V – 0.7 Ah
Remote controllable	Yes (TL-300)
Protection rating	IP42 - IK04
Electrical insulation	Class II
Applicable legislation	CE marking (93/68/CEE): 2014/35/EU 2014/30/EU 2011/65/EU

Photometric curve



DATA SHEET. Model: LLD-200B _ Rev. 01 (March 2024)




LUZNOR Desarrollos Electrónicos, S.L.
Paduleta, 47 · 01015 · Vitoria-Gasteiz · 945 200 961
NIF: B01266451 · luznor@luznor.com · www.luznor.com



Dimensions

Flush mounting (cut: 300 x 127 mm)



DATA SHEET. Model: LLD-200B _ Rev. 01 (March 2024)



LUZ NOR Desarrollos Electrónicos, S.L.
Paduleta, 47 · 01015 · Vitoria-Gasteiz · 945 200 961
NIF: B01266451 · luznor@luznor.com · www.luznor.com

