
DATA SHEET. Model: Matiz Self-contained.

Self-contained beacon light with maintained and nonmaintained functioning of the Matiz Series.





Description

Self-contained circular beacon light for flush mounting on a hollow surface by means of a spring kit or on a solid surface by means of a masonry box.

Composed of a central white LED and an ambient LED crown available in different colours.

Careful design with strong opal diffuser (-30%) for maximum light homogeneity.

Technical characteristics

Supply voltage	230 Vac - 50 Hz	
Autonomy	Charge in 24 h	1 h
	Charge in 48 h	2 h

0 ÷ 40°C

2014/35/EU 2014/30/EU 2011/65/EU

Ni-MH 3.6 V - 80 mAh

CE marking (93/68/CEE):

Mains power 0.5 W Electrical insulation Class II IP42 or IP55, IK08

Protection rating

Operation temperature

Battery Crown colours

B Y V A R N/A Remote controllable


Applicable legislation


Functions

central Crown
On
Off
On
Off

Dimensions


Surface mounting






Dimensions

Mounting with flushing frame



Flush mounting with masonry box



DATA SHEET. Model: Matiz Self-Contained _ Rev. 01 (March 2024)



LUZNOR Desarrollos Electrónicos, S.L.


Paduleta, 47 · 01015 · Vitoria-Gasteiz · 945 200 961 NIF: B01266451 · luznor@luznor.com · www.luznor.com







Installation Scheme



DATA SHEET. Model: Matiz Self-Contained _ Rev. 01 (March 2024)



