



PCM Series CENTRALIZED

Beacon light of reduced dimensions and industrial yet modern aesthetics. Composed of a low-power central LED available in different colours. Centralized (powered by a centralizing device) and with maintained operation. AISI 304 stainless steel body.



Maintained

model	power supply	RRP (€)
PCM-B0	12 Vdc or 12 Vac	31.59

To request different LED colour or different diffuser type, change the corresponding letters in the reference. Example:

LED colour | B □ Y ■ V ■ A ■ R ■
 PCM-YT
 Diffuser | T Transparent
 O Opal

- ◇ Fastening by means of adhesive paste or optional stainless steel nut M18x1:
Ref. M01388INOX
RRP. 3.39 €
- ◇ Stainless steel frames for universal boxes or other sizes available on request.

Centralizing devices

- ◇ The centralizing device powers the beacons at 12 Vdc, both in presence of the mains (maintained) and in emergency mode.
- ◇ Metal wall mounting cabinet with front door, epoxy painted grey RAL 7035.
- ◇ With remote control input.
- ◇ Ni-Cd (HT) battery.
- ◇ Each device can power a maximum number of beacons ensuring a 1 hour autonomy in emergency mode.

model	A (h)	beacons	dimensions (mm)	RRP (€)
EPM-24	1	24	400 x 300 x 150	525.70
EPM-64	1	64	400 x 300 x 150	629.89
EPM-112	1	112	400 x 300 x 150	840.15
EPM-224	1	224	500 x 400 x 200	1,387.07

Technical characteristics

- ◇ Electrical insulation Class III
- ◇ Remote controllable Yes (centralizing device)
- ◇ Protection rating IP67, IK08

Surface mounting

